

**THREE PHASE, TEFC SEVERE DUTY
ENERGY EFFICIENT - ALL CAST IRON**



eLINE Typical Performances @ 60HZ 208V

HP	NEMA Frame size	RPM		TORQUE [%]		AMPS			EFF [%]					Power Factor [%]					S.F.	NEMA Code Letter	NEMA Design	MAX KVAR	WK ² Lb-Ft ²	Net Weight Lbs	Bearing System	
		Syn.	Full Load	Locked Rotor	Break down	Full Load	Locked Rotor	@ SF	Gar EFF	Nema Nominal					1/4 Load	2/4 Load	3/4 Load	4/4 Load								5/4 Load
										1/4 Load	2/4 Load	3/4 Load	4/4 Load	5/4 Load											DE & ODE	
1	143T	1800	1755	295	310	3.1	21.7	4.2	80.4	63.8	76.8	81.0	82.5	82.7	34.0	53.0	66.0	75.0	80.0	1.40	L	B	0.8	0.08	60	6205 2Z C3
1	145T	1200	1155	180	290	3.3	14.7	4.4	77.7	66.2	76.8	79.7	80.0	79.0	33.0	52.0	65.0	73.0	78.0	1.40	H	B	0.9	0.13	61	6205 2Z C3
1.5	143T	3600	3500	275	320	4.2	29.7	6.0	80.4	63.1	77.5	81.4	82.5	82.4	51.0	72.0	81.0	87.0	89.0	1.30	K	B	0.8	0.06	60	6205 2Z C3
1.5	145T	1800	1745	265	370	4.6	28.8	6.0	82.0	69.6	80.0	83.2	84.0	83.5	38.0	59.0	71.0	79.0	83.0	1.40	K	B	1.0	0.09	63	6205 2Z C3
1.5	182T	1200	1175	255	350	5.2	29.7	6.4	83.7	68.8	80.5	84.2	85.5	85.6	32.0	49.0	63.0	72.0	77.0	1.40	K	B	1.3	0.34	93	6306 2Z C3
2	145T	3600	3505	280	325	5.3	40.2	7.5	82.0	72.6	81.4	83.8	84.0	83.3	51.6	71.8	82.0	87.0	91.0	1.40	K	B	1.0	0.06	66	6205 2Z C3
2	145T	1800	1735	240	330	5.8	33.3	8.0	82.0	73.6	82.0	84.0	84.0	83.1	44.0	65.0	76.0	82.0	86.0	1.40	J	B	1.2	0.11	65	6205 2Z C3
2	184T	1200	1165	210	270	6.4	31.8	8.2	84.8	77.2	85.8	87.1	86.5	85.3	34.0	55.0	67.0	74.0	78.0	1.30	H	B	1.6	0.40	107	6306 2Z C3
3	182T	3600	3510	220	280	8.9	49.9	10.6	83.7	72.9	82.1	84.8	85.5	84.9	51.0	71.0	80.0	86.0	88.0	1.40	J	B	1.5	0.12	89	6306 2Z C3
3	182T	1800	1745	260	380	8.8	55.7	10.4	85.9	76.9	85.1	87.3	87.5	86.9	43.0	64.0	76.0	82.0	85.0	1.30	K	B	1.8	0.24	100	6306 2Z C3
3	213T	1200	1170	230	350	9.3	56.1	11.5	85.9	75.5	84.3	86.9	87.5	87.0	37.0	56.0	68.0	76.0	80.0	1.30	K	B	2.2	0.66	144	6308 2Z C3
5	184T	3600	3500	225	280	13.4	79.6	18.1	85.9	80.0	86.3	87.8	87.5	86.7	58.0	75.0	85.0	87.0	90.0	1.40	H	B	2.4	0.20	115	6306 2Z C3
5	184T	1800	1735	250	320	13.8	81.4	17.7	85.9	80.3	86.9	88.7	87.5	86.6	52.0	70.0	81.0	86.0	88.0	1.30	J	B	2.5	0.34	117	6306 2Z C3
5	215T	1200	1155	190	250	14.4	72.3	18.6	85.9	81.9	87.2	88.4	87.5	85.7	44.0	66.0	76.0	82.0	84.0	1.30	H	B	3.0	0.82	165	6308 2Z C3
7.5	213T	3600	3500	220	350	18.6	101.3	25.4	87.0	83.2	88.2	89.0	89.5	87.0	67.0	83.0	89.0	92.0	93.0	1.30	G	B	2.7	0.36	155	6308 2Z C3
7.5	213T	1800	1750	200	280	19.8	111.8	25.9	88.1	84.9	89.5	90.2	89.5	87.8	55.0	75.0	84.0	87.0	89.0	1.30	H	B	3.5	0.72	163	6308 2Z C3
7.5	254T	1200	1180	260	220	20.8	107.1	27.4	88.1	84.0	88.4	89.7	89.5	88.2	55.0	73.0	82.0	86.0	86.0	1.30	G	B	3.7	3.27	284	6309 2Z C3
10	215T	3600	3495	235	260	25.1	144.5	32.3	88.1	86.3	89.9	90.3	89.5	88.3	69.0	84.0	90.0	92.0	92.0	1.30	H	B	3.6	0.43	178	6308 2Z C3
10	215T	1800	1745	180	220	26.3	142.0	35.8	88.1	87.1	90.7	90.8	89.5	87.2	59.0	77.0	86.0	88.0	89.0	1.30	H	B	4.5	0.87	182	6308 2Z C3
10	256T	1200	1175	255	270	27.5	136.0	33.0	88.1	85.6	89.5	90.1	89.5	88.1	54.0	73.0	81.0	85.0	86.0	1.20	G	B	5.2	3.27	297	6309 2Z C3
15	254T	3600	3540	230	240	38.8	188.1	51.5	88.9	84.3	89.4	90.4	90.2	89.4	54.0	74.0	82.0	86.0	86.0	1.30	F	B	7.4	1.15	284	6309 2Z C3
15	254T	1800	1760	220	265	37.5	191.7	47.1	89.8	86.3	90.5	91.0	91.0	89.8	62.4	81.5	87.4	90.0	89.9	1.30	G	B	6.0	2.52	293	6309 2Z C3
15	284T	1200	1175	265	210	40.0	205.5	49.1	88.9	86.4	90.3	90.8	90.2	88.7	56.0	75.0	83.0	86.0	86.0	1.20	G	B	7.4	4.75	380	6311 2Z C3
20	256T	3600	3540	235	260	50.5	238.7	67.2	88.9	86.8	90.9	91.1	90.2	88.7	60.0	79.0	85.0	87.0	87.0	1.30	F	B	9.4	1.47	332	6309 2Z C3
20	256T	1800	1755	220	240	49.3	249.4	58.8	89.8	88.8	92.1	91.9	91.0	89.8	68.0	85.0	89.0	91.0	91.0	1.20	F	B	7.5	3.06	359	6309 2Z C3
20	286T	1200	1175	250	210	53.8	261.7	62.4	88.9	86.8	90.3	91.0	90.2	88.6	58.0	76.0	84.0	86.0	86.0	1.20	G	B	9.8	5.17	397	6311 2Z C3
25	284TS	3600	3525	260	230	65.2	321.9	73.2	89.8	87.5	91.5	91.8	91.0	89.7	60.4	79.2	86.0	87.0	87.6	1.15	G	B	11.6	1.63	364	6311 2Z C3
25	284T	1800	1760	230	230	61.7	312.9	70.1	91.4	90.3	93.2	93.2	92.4	91.0	67.0	84.0	89.0	91.0	90.0	1.15	F	B	9.2	3.19	386	6311 2Z C3
30	286TS	3600	3535	245	290	76.1	361.7	82.3	89.8	85.4	90.5	91.3	91.0	90.2	63.9	81.5	86.4	88.0	88.5	1.15	F	B	13.3	1.92	417	6311 2Z C3
30	286T	1800	1755	235	230	75.2	383.4	84.5	91.4	90.7	93.4	93.3	92.4	91.0	68.0	85.0	90.0	92.0	90.0	1.15	G	B	10.4	3.59	424	6311 2Z C3